

MAGAZINE UNLOADER ESU-500/EUD-500C/ESU-500T

Designed to store the mounted PCB into the magazine rack at the end of the production line.



MODEL	CAPACITY	TYPE	DIMENSION (LxWxH)	WEIGHT(kg)
ESU-500	5racks UP:2 DOWN:3	SL	2150x830x1150	190
		YL	2550x910x1150	210
		LL	3130x1000x1150	230
		XL	3130x1070x1150	250
ESU-400	4racks UP:2 DOWN:2	SL	1730x830x1150	180
		YL	2150x910x1150	200
		LL	2530x1000x1150	220
		XL	2530x1070x1150	240

* Other requirement available upon your request



■ CE Appliance

MODEL	CAPACITY	TYPE	DIMENSION (LxWxH)	WEIGHT(kg)
EUD-500C	5racks UP:2 DOWN:3	SL	2150x830x1650	200
		YL	2550x910x1650	220
		LL	3130x1000x1650	240
		XL	3130x1070x1650	260
EUD-400C	4racks UP:2 DOWN:2	SL	1730x830x1650	190
		YL	2150x910x1650	210
		LL	2530x1000x1650	230
		XL	2530x1070x1650	250

* Other requirement available upon your request



■ Space Economized, T-type

MODEL	CAPACITY	TYPE	DIMENSION (LxWxH)	WEIGHT(kg)
ESU-500T	5racks UP:2 DOWN:3	SL	990x1950x1200	200
		YL	1190x2360x1200	220
		LL	1370x2760x1200	240
		XL	1460x2760x1200	260
ESU-400T	4racks UP:2 DOWN:2	SL	990x1540x1200	190
		YL	1190x1860x1200	210
		LL	1370x2160x1200	230
		XL	1460x2160x1200	250

* Other requirement available upon your request


Features

- Magazine change over time : 26sec (220V, 60Hz, 1Ph)
- Conveyor width adjustment by thumb screw locking (Only for ESU-500/400 model)
- Programmable Logic Controller
- Comforms to SMEMA Spec. 1.2

Options

- Touch screen
- Conveyor : Auto width adjustment
- Magazine change over time : 15sec (220V, 60Hz, 1Ph)
- Safety cover (Except EUD-500C model)

Operating Figure



ESU-500

