

MAGAZINE LOADER **ESL-500/ELD-500C/ESL-500T/ESL-200S**

Designed to load PCBs from magazine rack and deliver them into the next process.



MODEL	CAPACITY	TYPE	DIMENSION (LxWxH)	WEIGHT(kg)
ESL-500	5racks UP:2	SL	1630x830x1150	180
		YL	2030x910x1150	200
	DOWN:3	LL	2410x1000x1150	220
		XL	2410x1070x1150	240
ESL-400	4racks UP:2	SL	1210x830x1150	170
		YL	1530x910x1150	190
	DOWN:2	LL	1810x1000x1150	210
		XL	1810x1070x1150	230

* Other requirement available upon your request

■ CE Appliance

MODEL	CAPACITY	TYPE	DIMENSION (LxWxH)	WEIGHT(kg)
ELD-500C	5racks UP:2	SL	1630x830x1650	190
		YL	2030x910x1650	210
	DOWN:3	LL	2410x1000x1650	230
		XL	2410x1070x1650	250

* Other requirement available upon your request



★ Space Economized.

■ T-type

MODEL	CAPACITY	TYPE	DIMENSION (LxWxH)	WEIGHT(kg)
ESL-500T	5racks UP:2	SL	1100x1960x1200	190
		YL	1270x2360x1200	210
	DOWN:3	LL	1470x2760x1200	230
		XL	1560x2760x1200	250
ESL-400T	4racks UP:2	SL	1100x1540x1200	180
		YL	1270x1860x1200	200
	DOWN:2	LL	1470x2160x1200	220
		XL	1560x2160x1200	240

* Other requirement available upon your request

★ Space Economized.


■ Double pusher cylinder

MODEL	CAPACITY	TYPE	DIMENSION (LxWxH)	WEIGHT(kg)
ESL-200S	2racks UP:1	SL	830x870x1220	170
	DOWN:1			

* Other requirement available upon your request



Operating Figure



Features

- Magazine change over time : 26sec (220V, 60Hz, 1Ph)
- Able to link with vacuum pick up loader
- Programmable Logic Controller
- Comforms to SMEMA Spec. 1.2

Options

- Touch screen
- Magazine change over time : 15sec (220V, 60Hz, 1Ph)
- Safety cover (Except ELD-500C model)